AQUARIUS UF1802

The LICF 1802 is a pump filtration unit designed for the removal of waste water from material and personnel airlock shower trays. Fitted with a high capacity 18 litres/min quad diaphragm pump, to provide trouble free use, having the ability to self prime or run dry.

Two filter bottles are fitted prior to the pump to provide both filtration and protection from the pumps (20 micron and 5 micron). Connections are 3/4" BSP and the unit is activated by a safe air switch bellows that can be placed in the shower tray.

Benefits of the Aquarius UF1802

- * LIGHTWEIGHT
- ★ FLOW RATE 18 LITRE5/MIN
- ★ MANUFACTURED IN ABS PLASTIC
- ★ AVAILABLE IN 110v OR 230v



Aquarius UF1802 Technical Specifications

Specifications	Aquarius 1802
Capacity	18 litres/minute
Power supply	110 or 230 volts 2 amps
Dimensions	380(h) x 400(w) x 310(d)mm
Weight	14 kg
Waste filters	10" Cartridge 20μ and 5μ
Protection for Pumps	Inline quad filter of 20µ 2amp fuse
Pumps Waste 18 litres/min	18 litres/min
Operation	Depress the foot bellows.



For more information please visit us at www.mecanaka.co.uk



Tel: 02392 584414

Email: info@mecanaka.co.uk